

FUNCTION	DISPLAY	RANGE
SPEED	SPD	4-299 KPH/MPH
VOLTAGE	V	1.6-52.6 VAC/VDC
TEMPERATURE	ENG	0-260°C 32-499°F
MAINTENANCE REMINDER	OIL/CARE	0-9999 KM/M
DISTANCE	DST	0-29999 KM OR M
ACCUM. RUN TIME	CLOCK	0-9999 HOURS
ODOMETER	ODO	0-299999 KM OR M

POWER	DESCRIPTION
EXTERNAL POWER INPUT	9-400 VAC 9-55 VDC (NO POLARITY REQUIREMENTS.)
INTERNAL BATTERY	3V CR2032
BATTERY LIFE	1 YEAR
POWER WIRE	RED/BLACK 20G WIRE

FEATURES	
TEMPERATURE SENSOR	AMBIENT TEMPERATURE ENGINE TEMPERATURE
BACKLIGHT	5 LED GROUP
SCREEN	78.75 X 28.6MM (3.1 X 1.13")
PHYSICAL DIMENSIONS	106.93X59.46X23.7MM WXHxD (4.21X2.34X0.93" WXHxD)
PHYSICAL WEIGHT	3.9 OZ (110 GRAMS)
OPERATION TEMPERATURE	0-60°C (32-140°F)
STORAGE TEMPERATURE	-20-80°C (0-175°F)
CRITICAL ENVIRONMENT (TEMP)	AMBER/RED LED ALERTS