

<b>FUNCTION</b>	<b>DISPLAY</b>	<b>RANGE</b>	<b>FEATURES</b>	
SPEED	SPD	4-399 KPH/MPH	REAL-TIME RPM BAR GRAPH	0-12,000 RPMS
TACHOMETER	GRAPHICAL	0-12000 RPM	NUMERIC RPM READOUT	0-19,999 RPMS
TEMPERATURE	ENG	0-260°C 32-499°F	TEMPERATURE SENSOR	AMBIENT TEMPERATURE ENGINE TEMPERATURE
DISTANCE	DST	0-19999 KM OR M	BACKLIGHT	LED GROUP
ACCUM. RUN TIME	CLOCK	0-9999 HOURS	SCREEN	78.75 X 28.6MM (3.1 X 1.13")
ODOMETER	ODO	0-999999 KM OR M	PHYSICAL DIMENSIONS	106.93X59.46X23.7MM WXHXD (4.21X2.34X0.93" WXHXD)
RIDE TIME	RT	0-9999 HOUR 59 MIN	PHYSICAL WEIGHT	3.9 OZ (110 GRAMS)
ACCUM. RIDE TIME	ART	0-9999 HOUR 59 MIN	OPERATION TEMPERATURE	0-60°C (32-140°F)
12H OR 24H CLOCK	00:00:00	12:59:59 OR 24:59:59	STORAGE TEMPERATURE	-20-80°C (0-175°F)
LOW BATTERY	LO	ABOUT 1 YEAR LIFE	ENGINE ENVIROMENT (TEMP OR TACH)	AMBER/RED LED ALERTS
TIRE SIZE		0-3999MM		
ENGINE TEMP		-30C - 270C		
AMBIENT TEMP		-40C -125C		

<b>POWER</b>	<b>DESCRIPTION</b>
EXTERNAL POWER INPUT	9.0-400 VAC/VDC (NO POLARITY REQUIREMENTS.)
INTERNAL BATTERY	3V CR2032
BATTERY LIFE	1 YEAR
POWER WIRE	RED/BLACK 20G WIRE